RELOCATION

NELSON WORLDWIDE

RELOCATION

NELSON WOR

30 W MONROE

Nelco Architecture, Inc.

Illinois Design Firm Regist

: Date:

12/14/2023

RELOCATIO

30 W MONROE

SUITE 1710

CHICAGO IL, 60603

Sheet

DRAWING INDEX

NERAL

AN-0

AN-1

COVER SHEET

LIFE SAFETY PLA

AN-0

AN-1

AN-2

COVER SHEET

LIFE SAFETY PLAN

GENERAL NOTES

AN-1

AN-2

AN-3

LIFE SAFETY PLAN

GENERAL NOTES

SPECIFICATIONS

AN-2

AN-3

AN-4

GENERAL NOTES

SPECIFICATIONS

SPECIFICATIONS

AN-3

AN-4

AN-5

SPECIFICATIONS

SPECIFICATIONS

FINISH LEGEND

AN-4

AN-5

CHITECT

SPECIFICATIONS

FINISH LEGEND

RAL

CHITECT

A0-1

A1-1 RAL

DEMOLITION PLAN

CONSTRUCTION PLA

A0-1

A1-1

A2-1

DEMOLITION PLAN

CONSTRUCTION PLAN

REFLECTED CEILING PLA

A1-1

A2-1

A3-1

CONSTRUCTION PLAN REFLECTED CEILING PLAN

ELECTRICAL PLAN

A3-1

A4-1

A5-1

ELECTRICAL PL

FINISH PLAN

FURNITURE PL

A4-1

A5-1

A7-1

FINISH PLAN

FURNITURE PLAN

INTERIOR ELEVATI

A5-1

A7-1

A8-1

FURNITURE PLAN

INTERIOR ELEVATIONS

INTERIOR DETAILS

A7-1

A8-1

A9-1

INTERIOR ELEVATION

INTERIOR DETAILS

DOOR SCHEDULE, DO

A8-1

A9-1

INTERIOR DETAILS

DOOR SCHEDULE, DOOR & FRAMES, PARTITIONS

PROJECT DESCRIPTION

WORK TO BE PERFORMED IN AN EXISTING SPEC SUITE. WORK INCLUDES:

MINIMAL DEMOLITION, MININAL NEW CONTRUCTION INCLUDING PARTITIONS

AND MILLWORK, NEW FINISH APPLICATION, AND MINIMAL ELECTRICAL

CHANGES. NO CHANGES TO EXISTING TO REMAIN CEILING OR LIGHTING. NO

STRUCTURAL WORK IS REQUIRED.

4,413 S

BID ALTERNATES

ALT-1: (DEDUCT) NO NEW WALL TILE WORK AT PANTRY 1702. EXISTING TILE BACKSPLASH TO REMAIN.

ALT-2: (DEDUCT) EXISTING COUNTERTOP IN PANTRY 1702 MILLWORK WALL TO REMAIN.

SECTION 093000 - TILING

GENERAL

Submit samples for each type, composition of tile and for each color and finish

Furnish extra materials that match and are from same production runs as products installed. Furnish quantity of full-size tile and trim units equal to 3% of amount installed for each type, composition, color, pattern, and size indicated.

DUCTS

d.

Extend tile work into recesses and under or behind equipment and fixtures to form complete covering without interruptions. Jointing Pattern: Lay tile in grid pattern unless otherwise indicated. Lay out tile work and center tile fields in both directions ach space or on each wall area. Lay out tile work to minimize the use of pieces that are less than half of a tile.

Unless otherwise indicated, install tile with the following joint widths: glazed wall tile 1/16 inch, and porcelain tile: 1/4 inch.

Lay tile wainscots to dimensions indicated or to next full tile beyond dimensions indicated.

Unless otherwise indicated, install tile with the following joint widths: glazed wall tile 1/16 in

Lay tile wainscots to dimensions indicated or to next full tile beyond dimensions indicated.

Provide expansion joints and other sealant-filled joints, including control, contraction, and iso

SECTION 096513 - RESILIENT BASE AND ACCESSORIES

GENERAL

Height: As indicated on Drawin Outside Corners: Job formed. Inside Corners: Job formed. Outside Corners: Job formed. Inside Corners: Job formed. Colors and Patterns: As indicat

8.

Comply with manufacturer's written instructions for installing resilient base.

9.

Apply resilient base to walls, columns, pilasters, casework and cabinets in toe spaces, and other permanent fixtures in rooms and areas where base is required.

10.

Install resilient base in lengths as long as practical without gaps at seams and with tops of adjacent pieces aligned.

SECTION 096813 - TILE CARPETING **GENERAL** Maintain pile-direction patterns recommended in writing by carpet tile manufacturer. Extend carpet tile into toe spaces, door reveals, closets, open-bottomed obstructions, removable flanges, alcoves, and similar openings. Maintain reference markers, holes, and openings that are in place or marked for future cutting by repeating on carpet tile CARPET CPT-1 **CARPET** CPT-1 CPT-2 **CARPET** CPT-1 **SHAW** SHARE G228R **EMPATHY** 8'x10', HIDDEN EDGE **NELSON NELSON** N/A **ENTRY AREA RUG** CPT-2 **FLOR TERRAIN** 21-1534-02 **CHALK** 19.69" X 19.69" QUARTER TURNED **NELSON** GC jodi.consani@interface.com OPEN COLLAB AREA CPT-1 CPT-2 CPT-3 CPT-1 **SHAW** SHARE G228R **EMPATHY** 8'x10', HIDDEN EDGE **NELSON NELSON** N/A **ENTRY AREA RUG** CPT-2 **FLOR TERRAIN** 21-1534-02 **CHALK** 19.69" X 19.69" QUARTER TURNED **NELSON** GC jodi.consani@interface.com OPEN COLLAB AREA RUG CPT-3 **INTERFACE OPEN AIR 401** 106777

NICKEL

PLANK TO MATCH EXISTING

```
TO MATCH EXISTING
NELSON
GC
jodi.consani@interface.com
GENERAL CARPET
CHALK
NICKEL
CPT-2
FLOR
TERRAIN
21-1534-02
CHALK
19.69" X 19.69"
QUARTER TURNED
NELSON
GC
jodi.consani@interface.com
OPEN COLLAB AREA
CPT-3
INTERFACE
OPEN AIR 401
106777
NICKEL
PLANK TO MATCH EXISTING
TO MATCH EXISTING
NELSON
GC
jodi.consani@interface.com
GENERAL CARPET
TILE
TL-1
TILE
TL-1
TILE
TL-1
ELM SURFACES
SOHO; GLOSSY
BLUE
2" X 10"; 9.5MM THICKNESS
VERTICAL, STRAIGHT STACK; GROUT:
MERKRETE COLOR: D-525 BLACK SAPPHIRE
1/16" THICK
NELSON (TILE ONLY), GC (GROUT, ETC)
GC
NIKKI GRIECO 630 935 0842
CAFE BACKSPLASH
VINYL BASE
B-1
VINYL BASE
B-1
TARKETT
COVE AT HARD FLOOR, STRAIGHT AT
CARPET
80
ICICLE
4"H
GC
GC
BRIDGETTE O'CONNOR
815-219-8111
AS NOTED
B-2
TARKETT
COVE AT HARD FLOOR, STRAIGHT AT
BURNT UMBER
4"H
GC
```

GC **BRIDGETTE O'CONNOR** AS NOTED CARPET 815-219-8111 B-2 **TARKETT** COVE AT HARD FLOOR, STRAIGHT AT CARPET 63 **BURNT UMBER** 4"H GC GC **BRIDGETTE O'CONNOR** 815-219-8111 **AS NOTED** B-3 WOOD BASE PAINTED TO MATCH PARTITION 4"H GC GC N/A AS NOTED 18. REMOVE ALL ABANDONED TELEPHONE AND DATA 19 FLOORING AND WALL BASE TO REMAIN, U.N.O. **DEMOLITION GENERAL NOTES DEMOLITION PLAN KEYNOTES** 001 DEMOLISH EXSITING PARTITION. PATCH AND REPAIR CEILING AND FLOORING AS REQUIRED. 002 DEMOLISH EXISTING COAT ROD. PREP TO RECEIVE NEW MILLWORK SHELVING. 003 DEMOLISH EXISTING WALLCOVERING AND WALL BASE. PREP WALL TO RECEIVE NEW FINISH. DEMOLISH EXISTING WALL TILE. PREP WALL TO RECEIVE NEW TO RECEIVE NEW FINISH. 004 DEMOLISH EXISTING WALL TILE. PREP WALL TO RECEIVE NEW FINISH. MILLWORK, EQUIPMENT, AND PLUMBING TO REMAIN. 005 DEMO EXISTING CARPET AND WALL BASE. FINISH. MILLWORK, EQUIPMENT, AND PLUM 005 DEMO EXISTING CARPET AND WALL BASE. 006 DEMOLISH EXISTING WALL BASE. PREP WAL 005 DEMO EXISTING CARPET AND WALL BASE. DEMOLISH EXISTING WALL BASE. PREP WALL FOR NEW FINISH INSTALLTION. DEMO EXISTING FLOOR CORE. PATCH AND REPAIR CARPET AS INSTALLTION. 007 DEMO EXISTING FLOOR CORE. PATCH AND REPAIR CARPET AS REQUIRED. 008 DEMO EXISTING POWER/DATA AT THIS LOCATION. PREP WALL F NEW FINISH.

009

DEMOLISH EXISTING CARPET TILE. PREP FLOOR TO RECEIVE NEW FLOOR FINISH.

ARCHITECT BEFORE CONTINUING WITH ANY WORK.

11

VINYL BASE SHALL BE STRAIGHT BASE AT ALL LOCATIONS FOR CARPET AND COVE BASE AT RESILIENT FLOORS.

12

ALL ELECTRICAL PANELS IN THE CORRIDORS SHALL BE PAINTED TO MATCH THE ADJACENT WALL FINISH.

13.

FINISH FLOORING TO EXTEND FROM WALL TO WALL INCLUDING UNDER CABINETS AND UNDERCABINET EQUIPMENT.

14

ALL INTERIOR WALL & CEILING FINISHES AND TRIM OF PUBLIC AREAS 26.

WALLS TO BE PAINTED PT-1, U

27.

WALL BASE TO BE B-1, UNO.

FINISH PLAN KEYNOTES

400

FELT PANEL TO WRAP CORNER

401

NEW CARPET, CPT-2, TO BE INSTALLED INSET AND FLUSH TO EXISTING FLOOR FINISH.

402

AREA RUG, CPT-1, TO LAY ON TOP OF EXISTING LVT FLOORING.

FLOOR FINISH.

402

AREA RUG, CPT-1, TO LAY ON TOP OF EXISTING LVT FLOORING.

403

PATCH CARPET WITH ATTIC STOCK AS REQUIRED, POST REMOVA 402

AREA RUG, CPT-1, TO LAY ON TOP OF EXISTING LVT FLOORING.

403

PATCH CARPET WITH ATTIC STOCK AS REQUIRED, POST REMOVAL OF EXISTING WALL

404

DRAPERY LOCATION. SEE RCP FOR ADDITIONAL INFORMATION.